

# PRODUCT DATASHEET

## LVED PRO 40/220...240/950 CS

LEDVANCE LED DRIVER PRO CS | Constant Current - Indoor - on/off



### Areas of application

- Suitable for indoor SELV installations
- Suitable for LED luminaires and LED modules
- Suitable for build-in luminaires with adjustable current setting
- Suitable for luminaires of protection class II
- Hotels, shops, hospitality, residential interiors
- Offices
- Suitable for indoor applications

### Product benefits

- High flexibility due to adjustable output currents via dip switch
- Small housing for flexible luminaire designs
- High quality of light thanks to low output ripple current

### Product features

- Lifetime: up to 50,000 h (at max. tc temperature)
- Low ripple current < 4 %
- Power factor: 0.95
- Protection class II
- High reliability thanks to long lifetime
- Safety according to IEC/EN 61347-1, IEC/EN 61347-2-13, GB 19510.1, GB 19510.14
- EMC immunity according to CISPR15/EN 55015, IEC/EN 61547, IEC/EN 61000-3-2, GB/T17743, GB 17625.1
- Performance according to IEC 62384
- With CCC, CE, CB certificate
- RoHS compliant

## TECHNICAL DATA

### Electrical data

Nominal wattage	46.00 W
Nominal output power	45 W
Nominal voltage	220...240 V
Nominal output voltage	25...42 V
Input voltage AC	198...264 V
Nominal current	250 mA
Nominal output current	700 mA / 750 mA / 800 mA / 850 mA / 900 mA / 950 mA <sup>1)</sup>
Inrush current	30 A
Output current tolerance	±5 %
Mains frequency	50...60 Hz
Total harmonic distortion	10 %
Power factor $\lambda$	0.98
ECG efficiency	90 % <sup>2)</sup>
Galvanic isolation	SELV
Operating frequency	50/60 Hz

1) Output current selectable by DIP SWITCH

2) At full load

### Dimensions & Weight

Length	146.00 mm
Width	40.00 mm
Height	27.00 mm
Product weight	97.00 g

### Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Temperature range in operation	-20...+50 °C

### Capabilities

Dimmable	No
----------	----

Dimming interface	Not dimmable
Overheating protection	Automatic switch off, reversible
Overload protection	Yes
No-load proof	Yes
Short-circuit protection	Yes

### Certificates & Standards

Approval marks – approval	CB / CCC / CE / RoHS
Protection class	II
Type of protection	IP20

### LOGISTICAL DATA

Temperature range at storage	-40...+80 °C
------------------------------	--------------

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075240933	Unpacked 1	36 mm x 26 mm x 89 mm	84.00 g	0.08 dm <sup>3</sup>
4058075240940	Shipping box 40	218 mm x 212 mm x 152 mm	5048.00 g	7.02 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.